

# Flex-Rite™

Now Stocked in  
White • Blue  
Black • Yellow



## RWD

"Now Available"

## ... assemblies for immediate shipment!

This premium washdown hose is designed for **cleanup duties** in non-oily applications, dairies, creameries, breweries, food, beverage, meat and poultry processing plants. This premium quality hose is capable of handling hot water up to **300°F**. (Meets 3-A\* standards, USDA requirements and is FDA compliant). A chemically resistant hose, with a wrapped cover construction designed to provide excellent resistance to cuts and abrasion while providing handling stability.

### Features:

- FDA Approved Washdown
- 300 psi
- Chemical Resistant

### Applications:

- Washdown
  - Food, Beverage & Dairy
  - Craft Brewing & Spirits
- Sanitizing Transfer

MODEL	I.D.	O.D.	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT PER FT.	VACUUM IN HG.	LENGTH
RWD075	3/4"	1.35"	300 PSI	-	.41 LBS	-	200'
RWDB075	3/4"	1.35"	300 PSI	-	.41 LBS	-	200'
RWDBK075	3/4"	1.35"	300 PSI	-	.41 LBS	-	200'
RWDY075	3/4"	1.35"	300 PSI	-	.41 LBS	-	200'

**TUBE** White, FDA, 3-A, EPDM

**REINFORCEMENT** spiral-plied synthetic fabric, 4 plies

**RECOMMENDED CLEANING** CIP, COP

**COVER** White, Black, Blue EPDM, Wrapped Finish

**EMP. RANGE** -40 to 300°F

All R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21 177.2600, 3-A 18-03

**WARNING:** Work pressure ratings for all Flex-Rite™ brand hoses are based on 70°F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200°F contact manufacturer for suggestions.

### 50 ft. Assemblies

"standard assemblies" are fitted with 3/4" male pipe and 1/2" male pipe swivel.  
Note: Other lengths and colors are available.



## IWD Washdown



**IWD** an economical, high quality alternative to the RWD, delivers hot water up to **200°F**. The extruded construction provides excellent handling and flexibility. The abrasion resistant, non-marking cover maintains its sanitary appearance.

**For less critical applications where FDA requirements aren't a consideration**

MODEL	I.D.	O.D.	WORKING PRESSURE	WEIGHT PER FT.
IWD050	1/2"	0.84"	300 PSI	.26 LBS
IWD075	3/4"	1.17"	300 PSI	.40 LBS

Other Sizes and Colors Available

**TUBE** Black EPDM

**REINFORCEMENT** Two synthetic textile spiral cords

**COVER** White EPDM

**TEMP. RANGE** -20 to 200°F

