



...our most versatile hose!

Versatility makes this hose our most popular choice for **product** transfer and **CIP** applications. (Meets 3-A* standards, USDA requirements and is FDA compliant). Rated for full suction and discharge use up to 150 PSI. The specially compounded tube is engineered to handle high temperatures, will not impart taste or odor. A dual wire helix makes the RSD **extremely flexible** and easy to handle.

Features:

- High/Low Volume Suction & Transfer
- Multiple Colors for Dedicated Services
- Dual Helix
- Full Size Range
- Highly Flexible

Applications:

- Pump Suction & Discharge
- CIP
- Receiving Bay
- Load Cell
- Flow Panel
- Filling Machines
- Railcar
- Glycol Transfer

MODEL	I.D.	O.D.	WORKING PRESSURE	RADIUS	MIN. BEND	WT. PER FT.	IN HG.	LENGTH
CTSRSD050	1/2"	1.00"	150 PSI	2.0"	.32 lbs.	29"	100'	
CTSRSD075	3/4"	1.25"	150 PSI	2.0"	.57 lbs.	29"	100'	
CTSRSD100	1"	1.50"	150 PSI	3.0"	.91 lbs.	29"	100'	
CTSRSD150	1 1/2"	2.06"	150 PSI	4.0"	1.03 lbs.	29"	100'	
CTSRSD200	2"	2.57"	150 PSI	4.5"	1.32 lbs.	29"	100'	
CTSRSD250	2 1/2"	3.12"	150 PSI	5.5"	1.84 lbs.	29"	100'	
CTSRSD300	3"	3.74"	150 PSI	7.0"	2.55 lbs.	29"	100'	
CTSRSD400	4"	4.77"	150 PSI	10.0"	5.51 lbs.	29"	100'	
CTSRSD600	6"	6.75"	150 PSI	22.0"	5.42 lbs.	29"	100'	

TUBE White, FDA, 3-A*, Chlorobutyl

REINFORCEMENT Spiral-plied synthetic fabric with dual wire helix

RECOMMENDED CLEANING CIP, COP

COVER Gray, Blue, Red, EPDM w/white stripe

TEMP. RANGE -40 to 225° F

COLORS AVAILABLE Consult Factory



CTSRSD GRAY

***DEFAULT STOCKED COLOR**



Suction & Discharge RED

available in sizes: RSD150, 200, 250, 300



Suction & Discharge BLUE

available in sizes: RSD150, 200, 250, 300

ALL R-Series hose products meet/comply: USDA Class III requirements, FDA CFR Title 21.1772600, 3-A 18-03

*The 3-A 62-02, standard applies only to assemblies of 3/4" diameter and larger.

WARNING Working pressure ratings for all Flex-Rite™ brand hoses are based on 70° F (ambient temperature). Working pressure and vacuum ratings will decrease as temperatures increase. For "R" series applications that exceed 200° F contact manufacturer for suggestions.



**VIRGINIA
FLORIDA**

LOCATIONS

804-354-1511 | 2558 Turkey Creek Rd., Oilville, VA 23129
863-816-3509 | 3633 Century Blvd., Suite #2, Lakeland, FL 33811

ASRSD817