Description codes

O	D	A	D	C 0 1	A	C	A	F	1	0 0 0	/	B	A	S S

(1) Pump Range
Twin Screw Pump

(2) Pump Size & Displacement
- D OS 22
- E OS 24
- F OS 26
- G OS 32
- H OS 34
- J OS 36
- K OS 42
- L OS 44
- M OS 46

(3) Port Size
- A 50mm Front / 40mm Top
- B 50mm Front / 50mm Top
- C 50mm Top / 50mm Front
- D 65mm Top / 50mm Front
- E 65mm Front / 50mm Top
- F 65mm Front / 40mm Top
- G 65mm Front / 65mm Top
- H 65mm Top / 65mm Front
- J 80mm Front / 40mm Top
- K 80mm Front / 50mm Top
- L 80mm Front / 65mm Top
- M 80mm Front / 80mm Top
- N 80mm Top / 80mm Front
- O 100mm Top / 65mm Front
- P 100mm Top / 80mm Front
- Q 100mm Front / 80mm Top
- R 100mm Top / 100mm Front
- S 100mm Front / 100mm Top
- T 150mm Front / 80mm Top
- U 150mm Front / 100mm Top
- V Rect Front / 40mm Top
- W Rect Front / 50mm Top
- X Rect Front / 65mm Top
- Y Rect Front / 80mm Top
- Z Rect Front / 100mm Top

(4) 4 - Port Type
- D IDF
- E RJT
- J SMS
- L DIN11851
- M Tri-Clamp (ASME)
- O Tri-Clamp (DIN32676)
- 3 DIN11864-1 Form A Range A
- 7 DIN11864-1 Form A Range C
- 1 DIN11864-2 Form A Range A
- 2 DIN11864-2 Form A Range C

(5-7) Product Seal

C01	Single Mechanical Seal	SC/C	EPDM
C02	Single Mechanical Seal	SC/C	FPM
C03	Single Mechanical Seal	SC/C	FFPM
C11	Single Mechanical Seal	SC/SC	EPDM
C12	Single Mechanical Seal	SC/SC	FPM
C13	Single Mechanical Seal	SC/SC	FFPM
D01	Single Flushed Mechanical Seal BSP	SC/C	EPDM
D02	Single Flushed Mechanical Seal BSP	SC/C	FPM
D03	Single Flushed Mechanical Seal BSP	SC/C	FFPM
D11	Single Flushed Mechanical Seal BSP	SC/SC	EPDM
D12	Single Flushed Mechanical Seal BSP	SC/SC	FPM
D13	Single Flushed Mechanical Seal BSP	SC/SC	FFPM
D51	Single Flushed Mechanical Seal NPT	SC/C	EPDM
D52	Single Flushed Mechanical Seal NPT	SC/C	FPM
D53	Single Flushed Mechanical Seal NPT	SC/C	FFPM
D61	Single Flushed Mechanical Seal NPT	SC/SC	EPDM
D62	Single Flushed Mechanical Seal NPT	SC/SC	FPM
D63	Single Flushed Mechanical Seal NPT	SC/SC	FFPM
F01	Double Flushed Mechanical Seal BSP	SC/C vs SC/C	EPDM
F02	Double Flushed Mechanical Seal BSP	SC/C vs SC/C	FPM
F03	Double Flushed Mechanical Seal BSP	SC/C vs SC/C	FFPM
F11	Double Flushed Mechanical Seal BSP	SC/SC vs SC/C	EPDM
F12	Double Flushed Mechanical Seal BSP	SC/SC vs SC/C	FPM
F13	Double Flushed Mechanical Seal BSP	SC/SC vs SC/C	FFPM
F51	Double Flushed Mechanical Seal NPT	SC/C vs SC/C	EPDM
F52	Double Flushed Mechanical Seal NPT	SC/C vs SC/C	FPM
F53	Double Flushed Mechanical Seal NPT	SC/C vs SC/C	FFPM
F61	Double Flushed Mechanical Seal NPT	SC/SC vs SC/C	EPDM
F62	Double Flushed Mechanical Seal NPT	SC/SC vs SC/C	FPM
F63	Double Flushed Mechanical Seal NPT	SC/SC vs SC/C	FFPM

(8) Screws
- A Standard 150°C
- B Hardened 150°C

(9) Spline/Cover Sealing
- C EPDM
- D FPM
- E FFPM
- G EPDM USP Class VI

(10) Front Cover
- A Plain Cover

(11) Surface Finish & Treaceability
- A Standard
- C Electropolish to 0.38 Ra
- F Standard with Traceability to EN10204 3.1
- H Electropolish to 0.38 Ra with Traceability to EN10204 3.1
- J Standard with Hydrostatic Test
- K Electropolish to 0.38 Ra with Hydrostatic Test
- L Standard with Traceability to EN10204 3.1 with Hydrostatic Test
- S Electropolish to 0.38 Ra with Traceability to EN10204 3.1 with Hydrostatic Test

(12) Jackets
- 1 None
- 2 Heating Pump Casing

(12) Shaft Type / Lubrication
- A Stainless Steel FDA Oil filled gearbox

(13-15) Special Options
- 000 No Special Options

(16) Delineator
- / AL Brand

(17) Shaft Position
- A LSD Front Inlet / Top Outlet
- B LSD Top Inlet / Front Outlet

(19-20) Paint
- SS Stainless Steel