



Alfa Laval LKH

Performance curves


LKH-5, 60 Hz

Motor:	3600 rpm. synchron.
Tolerance:	±5%
Impeller, Max. dia.:	5.197"
Impeller, Min. dia.:	3.54"
Pump inlet, dia.:	2", DN 50
Pump outlet, dia.:	1½", DN 40
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 3.4 Hp, 3460 rpm. asynchron., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-5, 60 Hz

Motor:	1800 rpm. synchr
Tolerance:	±5%
Impeller, Max. dia.:	5.197"
Impeller, Min. dia.:	3.54"
Pump inlet, dia.:	2", DN 50
Pump outlet, dia.:	1½", DN 40
Performance data refer to water at 68 °F	

 **Note!** The curves refer to motor: 1.7 Hp, 1700 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-10, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	6.417"
Impeller, Min. dia.:	4.331"
Pump inlet, dia.:	2½", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 11.5 Hp, 3500 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-10, 60Hz

Motor:	1800 rpm. synchron.
Tolerance:	±5%
Impeller, Max. dia.:	6.417"
Impeller, Min. dia.:	5.512"
Pump inlet, dia.:	2½", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	

 **Note!** The curves refer to motor: 2.4 Hp, 1750 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-15, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	5.433"
Impeller, Min. dia.:	4.724"
Pump inlet, dia.:	4"
Pump outlet, dia.:	3"
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 11.5 Hp, 3455 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-15, 60 HZ

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	5.433"
Impeller, Min. dia.:	4.72"
Pump inlet, dia.:	4"
Pump outlet, dia.:	3"
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 2.4 Hp, 1710 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-20, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	6.496"
Impeller, Min. dia.:	4.724"
Pump inlet, dia.:	2½", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 16.8 Hp, 3500 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-20, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	6.496"
Impeller, Min. dia.:	5.512"
Pump inlet, dia.:	2½", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 2.4 Hp, 1750 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR



A = 6.496" D = 5.512"
 B = 6.299"
 C = 5.906"


LKH-25, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.070"
Impeller, Min. dia.:	6.299"
Pump inlet, dia.:	3", DN 80
Pump outlet, dia.:	2½", DN 65
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 33.5 Hp, 3545 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with:
 - 3% for 16.8-28.2 Hp.
 - 5% for 8.5-11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR




LKH-25, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.070"
Impeller, Min. dia.:	6.299"
Pump inlet, dia.:	3", DN 80
Pump outlet, dia.:	2½", DN 65
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 4.7 Hp (3.5 kW), 1720 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with 3%.

DO NOT FORGET THE SAFETY FACTOR



LKH-35, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.661"
Impeller, Min. dia.:	6.69"
Pump inlet, dia.:	2.5", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	




Note! The curves refer to motor: 28.2 Hp, 3535 rpm. asynchr., 60 Hz.

For smaller motors, reduce head (H) with:

- 3% 16.8-22.8 Hp.

- 3% 8.5-11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR




LKH-35, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.661"
Impeller, Min. dia.:	6.69"
Pump inlet, dia.:	2½", DN 65
Pump outlet, dia.:	2", DN 50
Performance data refer to water at 68 °F	

 **Note!** The curves refer to motor: 3.4 Hp, 1720 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with 3%

DO NOT FORGET THE SAFETY FACTOR




LKH-40, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	9.291"
Impeller, Min. dia.:	6.693"
Pump inlet, dia.:	3", DN 80
Pump outlet, dia.:	2", DN 65
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 33.5 Hp, 2940 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with:
- 3% for 16.8-28.2 Hp.
- 5% for 11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR



A = 9.252" D = 8.268" G = 7.087"
B = 9.055" E = 7.874" H = 6.693 "
C = 8.661" F = 7.480"


LKH-40, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	9.291"
Impeller, Min. dia.:	7.480"
Pump inlet, dia.:	3", DN 80
Pump outlet, dia.:	2", DN 65
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 8.5 Hp, 1750 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with 5%

DO NOT FORGET THE SAFETY FACTOR




LKH-45, 60 Hz

Motor:	3600 rpm. synchron.
Tolerance:	±5%
Impeller, Max. dia.:	7.008"
Impeller, Min. dia.:	5.512"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 33.5 Hp, 3545 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with:
 - 3% for 16.8-28.2 Hp.
 - 5% for 8.5-11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR



A = 7.008" D = 5.906"
 B = 6.693" E = 5.512"
 C = 6.299"


LKH-45, 60Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	7.008"
Impeller, Min. dia.:	5.512"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 4.7 Hp, 1720 rpm. asynchr., 60 Hz.
For smaller motors.

DO NOT FORGET THE SAFETY FACTOR



LKH-50, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.070"
Impeller, Min. dia.:	5.906"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	




Note! The curves refer to motor: 33.5 Hp, 3500 rpm. asynchr., 60 Hz.

For smaller motors, reduce head (H) with:

- 3% for 16.8-28.2 Hp.
- 5% for 8.5-11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR




LKH-50, 60Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.070"
Impeller, Min. dia.:	6.693"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	

 The curves refer to motor: 6.0 Hp, 1750 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with 5%

DO NOT FORGET THE SAFETY FACTOR



LKH-60, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.268"
Impeller, Min. dia.:	6.299"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	6", DN 150
Performance data refer to water at 68 °F	




Note! The curves refer to motor: 46.9 Hp, 3500 rpm. asynchr., 60 Hz.

For smaller motors, reduce head (H) with:

3% for 16.8-28.2 Hp.

6% for 8.5-11.5 Hp.

DO NOT FORGET THE SAFETY FACTOR



A = 8.268" D = 7.087"
 B = 7.874" E = 6.693"
 C = 7.480" F = 6.299"


LKH-60, 60Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	8.268"
Impeller, Min. dia.:	6.299"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	6", DN 150
Pump outlet, dia.:	4", DN 100
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 8.5 Hp, 1750 rpm. asynchr., 60 Hz. For smaller motors, reduce head (H) with 5%.

DO NOT FORGET THE SAFETY FACTOR




LKH-70, 60 Hz

Motor:	3600 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	11.024"
Impeller, Min. dia.:	7.874"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	

 **Note!** The curves refer to motor: 115.3 Hp, 3565 rpm. asynchr., 60 Hz.
For smaller motors, reduce head (H) with: -3%.

DO NOT FORGET THE SAFETY FACTOR




LKH-70, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	11.024"
Impeller, Min. dia.:	7.874"
Pump inlet, dia.:	4", DN 100
Pump outlet, dia.:	3", DN 80
Performance data refer to water at 68 °F	

 **Note!** The curves refer to max. motor: 22.8 Hp, 1750 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



LKH-75, 60 Hz


Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	13.7"
Impeller, Min. dia.:	8.7"
Pump inlet, Dia.:	4" DN100
Pump outlet, Dia.:	4" DN100

Performance data refer to water at 68°F (20°C).



Note! The curves refer to max. motor: 40 Hp (30 kW), 1775 rpm. asynchr., 60 Hz. If Clear Flow impeller is mounted the performance can be up to 10% lower than on the curves shown.

DO NOT FORGET THE SAFETY FACTOR.




LKH-90, 60 Hz

	60 Hz
Motor:	1800 rpm. synchr.
Tolerance:	±5%
Impeller, Max. dia.:	13.7"
Impeller, Min. dia.:	11.81"
Pump inlet, dia.:	6", DN 150
Pump outlet, dia.:	6", DN 150
Performance data refer to water at 68 °F	



Note! The curves refer to motor: 75 kW, 1490 rpm. asynchr., 50 Hz. For smaller motors, reduce head (H) with: 3%.

DO NOT FORGET THE SAFETY FACTOR



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com