



Alfa Laval OptiLobe

Product description

L22	-	15	-	M	-	Q02	-	A	-	A	-	A	-	A
1		2		3		4		5		6		7		8

1 MODEL SIZE

L12
L13
L22
L23
L32
L33
L42
L43
L52
L53

2 PORT SIZE

10 (25 mm) 1"
15 (40 mm) 1½"
20 (50 mm) 2"
25 (65 mm) 2½"
30 (80 mm) 3"
40 (100 mm) 4"

3 MODEL SIZE

M = Triclamp

4 SEAL /ELASTOMER

Q02 - Easy Fit SS/C FPM
Q06 - Easy Fit SS/C EPDM
Q12 - Easy Fit SC/C FPM
Q16 - Easy Fit SC/C EPDM
Q22 - Easy Fit SC/SC FPM
Q26 - Easy Fit SC/SC EPDM
S02 - Easy Fit SS/C Flush FPM
S06 - Easy Fit SS/C Flush EPDM
S12 - Easy Fit SC/C Flush FPM
S16 - Easy Fit SC/C Flush EPDM
S22 - Easy Fit SC/SC Flush FPM
S26 - Easy Fit SC/SC Flush EPDM

5 ROTOR TYPE & CLEARANCE

A = SS Trilobe (8 bar, 130°C, 266°F)

6 SHAFT POSITION

A - Vertical Left Side Drive
B - Vertical Right Side Drive
C - Horizontal Bottom Drive
D - Horizontal Top Drive

7 SURFACE FINISH

A = Standard 32 Ra

8 ELASTOMER

A = No Options

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

200007233-1-EN-US

© Alfa Laval Corporate AB

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com